TOPLOADER ECO

This is our spray washing system which is highly efficient and economic and includes a lot of standard equipment which makes it very attractive.

The ECO model of our standard spray washing system is produced in the same high quality as all of our spray washers.

It has a more simple construction and includes several options to ensure the same cleaning results as our PRO models.

The spraywasher is only available in one size, and it is aimed at low cost operations, mainly related to maintenance and service operations.

Available options

- Filtration system
- Automatic water filling
- Automatic chemical dosing
- Extraction fan
- Integrated stainless steel coarse filter
- Stainless steel baskets and fixtures
- Digital control panel.

MODEL	AT 750 ECO
Volume	150 L
Basket size	Ø750 mm
Cleaning height max.	540 mm
Weight capacity max.	150 kg
Pump flow	250 l/min
Pump pressure	2.4 - 3.2 bar
Power supply	32 A
Heating effect	9000 W
Temperature	20 - 60 °C







✓ 100 % stainless steel construction Produced with a stainless steel cabinet, tank cover, electrical cabinet, pumps and heating elements.

√ Level sensor

Used for protection of heating elements and stainless steel pump.

√ CE - European Machine Directive

The spraywasher is produced in accordance with the European Machine Directive.

√ Motordriven rotating basket

The motordriven rotation ensures reliable cleaning results every time regardless of the geometry and size of the parts.

✓ Prepared for extra options

It is prepared for oil skimmer, automatic water filling, extraction fan and filtration system.

√ Adjustable machine feet

Adjustable stainless steel machine feet, and can also be supplied on wheels.

√ User-friendly analog control

Simple and reliable user-interface that makes it easy to operate.

√ Highly efficient spraying system

Produced with a high flow spraying system combining flat-jet nozzles and point nozzles from all angles inside the machine.

√ Including basket

A stainless steel basket is included, and specially designed baskets are available upon request.